RACU 5 DEACTIVATION

NOTE
This procedure assumes that MDM N1-2 is Primary and MDM N1-1 is Secondary.

1. INHIBIT NCS AUTORETRY

PCS Node 1: C&DH: MDM N1-1
Secondary NCS MDM Node 1
'Software Control'

sel MDM Utilities
sel Commands

cmd Second_NCS_Inh_NCS_Retry **Execute**

Secondary_NCS_MDM_Utilities

√Auto Retry Inhibit - X

2. COMMAND N1-2 TO DIAGNOSTICS

NOTE
1. Expect 'Disconnect' message on PCS.
2. Possible PDI DECOM fail message.

Node 1: C&DH: MDM N1-2
Primary NCS MDM Node 1
'MDM Major State'

sel Commands
cmd N1_2_MDM_Cmd_Xsitn_Dgnstc_State_Arm **Execute**
cmd N1_2_MDM_Xsitn_Dgnstc_State **Execute**

3. TELEMETRY RECOVERY ON OIU

CRT SM 212 OIU

BUS 4 BC - ITEM 15 EXEC (*)
BUS 3 RT - ITEM 10 EXEC (*)

Change OIU N1 Phys Dev to N1-1 - ITEM 18 +4 EXEC

Wait 1 minute from diagnostic command.

CRT Reload OIU Format 2 - ITEM 1 +2 EXEC

4. TELEMETRY RECOVERY ON PCS

PCS On PCS attached to PDIP N1-2 port

sel icon to open PCS CDS Main Control Panel Window
√Status box - yellow
sel 'Connect to MDM'
√Status box - green

Verify 'connected to MDM' indicated.

Home page will display when load complete (~1 minute).

NOTE
Expect PCS FDA 'CDH MDM N1-1 Detected RT Fail MDM N1-2 - PMA1'.

Node 1: C&DH: MDM N1-1
Primary NCS MDM Node 1
'MDM Major State'

√State - Primary

```
**********************************************
*  If State not Primary or no N1-1 TLM    *
*                                         *
*     √MCC                                *
* ******************************************* *
```

5. REMOVE POWER FROM N1-2 MDM AT RPC

NOTE
Expect PCS FDA (LED and message only) when MDM power removed.

Node 1: EPS: RPCM N1RS2 C
'RPCM N1RS2 C'

sel RPC 13
sel Commands
cmd Open **Execute**
√Position - Op

6. DISABLE RT DEVICES I/O ON EPS BUSES

PCS Node 1: C&DH: MDM N1-1
Primary NCS MDM Node 1

sel UB EPS_N1 23
sel RT Status
sel Inhib_RT Commands

PRIM_NCS_UB_EPS_N1_23_Inhib

cmd Inhib_RPCM_N1RS2_A **Execute**
cmd Inhib_RPCM_N1RS2_B **Execute**
cmd Inhib_RPCM_N1RS2_C **Execute**

PRIM_EPS_N1_23_RT Status

√RT Inhibit 20, 19, 18 (three) - X

7. COMMAND FGB RACU-5 OFF

NOTE
RACU commands sent from orbiter will not work if FGB relay matrix is in **MCC-M** command state (COMMANDING - INH). Crew can follow ground activities using the "If ENA" block below.

CRT SM 204 FGB

√COMMANDING - INH (Moscow Commanding)

If COMMANDING - INH

Crew ⇓ **MCC-H**, "Ready for RACU 5 Power Off."
MCC-H ⇒ **MCC-M**, "Go for RACU 5 Power Off."

RUSSIAN GROUND	AOS	LOS
Pass 1	___/___:___:___	___/___:___:___
Pass 2	___/___:___:___	___/___:___:___

MCC-M ⇒ **MCC-H** ⇑ crew,
"RACU 5 Powered Off at __/___:___:__GMT."

If COMMANDING - ENA

MCC-M ⇒ **MCC-H**, "Go for RACU 5 Power Off."
MCC-H ⇑ crew, "Moscow GO for RACU 5 Power Off."

On MCC GO

MCDS SM 204 FGB

RACU 5 Power OFF VIA NCS - ITEM 6 EXEC
√RACU 5 Input Amps < 2.0 A
√Output Volts ~0.0 V
√RACU 5 Power Off - ∗

PCS

FGB: EPS
FGB: EPS: RACU Details
RACU Details

sel Commands
cmd RACU 5 - Off **Execute**
√RACU 5 Converter - Off
√RACU 5 Input Current < 2.0 A
√Output Voltage ~0.0 V